


COMPONENT LIST			
L" DIM.	ITEM	MAKE FROM	DESCRIPTION
		P/N FT XX 6X24	CO WIRE .196 DIA.
2"		2X6X24	
4"		4X6X24	
6"		6X6X24	

GENERAL NOTES:

- A) MATERIAL TO BE HOT DIPPED, PRE-GALVANIZED STEEL, ASTM A641, TO AVOID THE FORMATION OF ZINC WHISKERS.
- B) FINISH:
1) POLYESTER POWDER COATING 1.2 - 3.0 MILS THICK.
- C) DIMENSIONAL TOLERANCES
1) GENERAL DIMENSIONS +/- 1/8" U.N.D.
2) LENGTH +/- 1/4"
3) WIDTH +/- 1/8"
4) DEPTH +/- 1/8"
5) ANGULAR FORMATION +/- 3 DEG.
6) CAMBER SHALL NOT EXCEED 1/2" ON STANDARD 10' LENGTH.
7) TWIST SHALL NOT EXCEED 1/2" ON STANDARD 10' LENGTH
- D) RIB VICE DIAMETER
1) .197 (5MM) DIAMETER.
- E) LONGITUDINAL WIRE DIAMETER.
1) .197 (5MM) DIAMETER
- F) CROSS SECTION AREA
AREA = (20 WIRES X .0438 IN²) = .876 IN²
UL MARKING = .8 IN²

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES.				DEBUR AND BREAK SHARP EDGES			
REVISION	NAME	CHANGE	DATE			TITLE: FLOORFLEX-TRAY	
A	AF		3-27-10				
						DWG. NO. FT XX 6 X 24	
						SCALE:1:1	
						SHEET 1 OF 1	